



1200VDC/500VAC/1600V _{PEAK} *				
CAP (MFD)	T MAX	H MAX	I peak (A)	ESR (mΩ)
0.15	0.550" (14.0mm)	1.050" (26.7mm)	190	7.5
0.18	0.600" (15.2mm)	1.050" (26.7mm)	230	6.4
0.22	0.650" (16.5mm)	1.050" (26.7mm)	290	5.4
0.27	0.700" (17.8mm)	1.050" (26.7mm)	350	4.5
0.33	0.800" (20.3mm)	1.050" (26.7mm)	430	3.9
0.39	0.900" (22.9mm)	1.400" (35.6mm)	510	3.4
0.47	0.900" (22.9mm)	1.400" (35.6mm)	610	3.0
0.56	0.950" (24.1mm)	1.400" (35.6mm)	730	2.6
0.68	1.100" (27.9mm)	1.400" (35.6mm)	880	2.3
0.82	1.250" (31.8mm)	1.800" (45.7mm)	1060	2.2
1.00	1.300" (33.0mm)	1.800" (45.7mm)	1300	1.8
1.20	1.350" (34.3mm)	1.800" (45.7mm)	1560	1.7
1.50	1.600" (40.6mm)	2.200" (55.9mm)	1940	1.5
1.75	1.700" (43.2mm)	2.200" (55.9mm)	2270	1.4
2.00	1.900" (48.3mm)	2.200" (55.9mm)	2590	1.3

* SEE "RATED VOLTAGE" SECTION ON PAGE 5 FOR DETAILS AND CONDITIONS REGARDING VOLTAGE RATINGS AT TOP OF TABLE.