

DC CONNECTIONS

3-Wire ConnectPro™ Charging / Trolling System

Exclusive Locking Plug and Receptacle Provides a Superior Electrical Connection for Trolling Motors



The ConnectPro™ system has superior electric current carrying capacity that eliminates problems that rob motors of power and reduce battery life.

PATENTED

12VBR

ConnectPro Receptacle

- Universal design for 2 or 3-wire configuration 12, 24, 12/24, 24/36 or 36 volt systems
- Watertight sealing cap
- Corrosion resistant, plated brass electrical components
- Drain holes in receptacle keep water away from electrical components
- Perma-Lock™ screw terminals will not loosen under extreme hull vibration
- Standard 1-1/8" diameter mounting hole
- Easy to install, with supplied mounting plate for front panel installation, or locking ring for rear access installation
- Accepts 10 and 8 gauge wire
- Easily replaces other trolling motor plugs and receptacles
- Available as OEM bulk pack part #: 12VBR.OEM

12VBP

ConnectPro Plug

- O-ring seal for waterproof connections
- Weather resistant plug cover
- Corrosion resistant, plated brass electrical components
- Accepts 16 to 8 gauge wire
- Ergonomic contoured grip for easy hook-up and ground blade alignment
- Available as OEM bulk pack part #: 12VBP.OEM



Plug "Locks" into Receptacle and Provides a Waterproof Seal



Use with 12/24 Volt 3-wire systems or 12/24/36 Volt 2-wire systems



12VCP

ConnectPro Receptacle & Plug

- 12VBR and 12VCP packaged together

12VBRAD

6 Gauge Wire Receptacle Adapter

- Allows 6 gauge wire connection to ConnectPro receptacle
- Corrosion resistant, plated brass electrical components
- Easy to Install
- Available as OEM bulk pack part #: 12VBRAD.OEM



6 Gauge Wire Receptacle Adapter

12VCP6

ConnectPro Receptacle, Plug and 6 Gauge Adapter

- 12VBR and 12VCP and 12 VBRAD packaged together

